



Productos



Soluciones



Soporte



Socio

Noticia &
EventosQuién
Somos

Latin America - Español



HAC-B2A51

5MP HDCVI Fixed IR Bullet Camera

* The parameters and datasheets below can only be applied to A51-S2 series

* In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.

- > Max. 25 fps@5MP (16:9 video output)
- > CVI/CVBS/AHD/TVI switchable
- > 3.6mm fixed lens (2.8 mm optional)
- > Max. IR length 20 m, Smart IR
- > IP67, DC12V





Especialización

Accesorios

Descargar

Camera

Image Sensor	1/2.7" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Pixel	5MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25–1/100000 s NTSC: 1/30–1/100000 s
Min. Illumination	0.02 Lux/F2.0, 30IRE, 0 Lux IR on
S/N Ratio	More than 65 dB
Illumination Distance	20 m (66 feet)
Illuminator On/Off Control	Auto;manual

Lens

Lens Type	Fixed lens / Fixed iris
Mount Type	M12
Focal Length	3.6 mm (2.8 mm Optional)
Max Aperture	F2.0
Angle of View	2.8 mm: 125° × 106° × 56° (diagonal × horizontal × vertical) 3.6 mm: 104° × 88° × 46° (diagonal × horizontal × vertical)
Focus Control	N/A
Close Focus Distance	2.8 mm: 0.8 m (2.6 ft) 3.6 mm: 1.2 m (3.9 ft)

DORI distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	56.0 m (183.7 ft)	22.4 m (73.5 ft)	11.2 m (36.7 ft)	5.6 m (18.4 ft)
	3.6mm	80 m	32 m	16 m	8 m (26.2 ft)





Productos



Soluciones



Soporte



Socio

Noticia &
EventosQuién
Somos

Latin America - Español

Pan/Tilt/Rotation

Tilt: 0° – 90°

Rotation: 0° – 360°

Video

Resolution

5M(2880×1620);4M(2560×1440)

1080P (1920 × 1080); 960H (960 × 576/960 × 480)

CVI:

PAL:5M@25 fps; 4M@25fps; 1080P@25fps

NTSC:5M@25 fps; 4M@30fps; 1080P@30fps

AHD:

PAL:4M@25 fps;

NTSC:4M@30 fps;

TVI:

PAL:4M@25 fps;

NTSC:4M@30 fps;

CVBS:

960H;

Frame Rate

Video Output

Video output choices of CVI/TVI/AHD/CVBS
by one BNC port

Day/Night

Auto (ICR) / Manual

OSD Menu

Multi-language

BLC Mode

BLC / HLC / DWDR

WDR

DWDR

Gain Control

AGC

Noise Reduction

2D

White Balance

Auto;manual

Smart IR

Yes

Mirror

Off/On

Privacy Masking

Off / On (8 area, rectangle)

Certifications

Certifications

CE (EN55032, EN55024, EN50130-4, EN60950-1,

EN 62368-1:2014+A11:2017)

FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)

Interface

Audio Interface

N/A

Electrical

Power Supply

12V DC ±30%



	-40°C to +60°C (-40°F to +140°F) / Less than 95% RH
Operating Conditions	* Start up should be done at above -40°C (-40°F)
Storage Conditions	-40°C to +60°C (-40°F to +140°F) / Less than 95% RH
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Aluminium
Dimensions	70.1 mm × 70.1 mm × 157.6 mm (2.76" × 2.76" × 6.21")
Net Weight	0.24 kg (0.53 lb)
Gross Weight	0.34 kg (0.75 lb)

Boletín

Entregar

Ingresa tu dirección de correo electrónico para recibir las últimas noticias e información de productos

[Cookies statements](#)
[Cookies setting](#)

Productos	Soluciones	Soporte	Socio	Noticia & Eventos	Quién somos
Network Cameras	Transportation	Tools	Dahua ECO		
HDCVI Cameras	Critical Infrastructure	Centro de descargar	Partner Program	Comunicado de prensa	Introducción
PTZ Cameras	Traffic	Capacitación		Casos exitosos	Contáctenos
Thermal Cameras	Banking & Finance	RMA		Eventos	Trust Center
	Building	Video			Terms of Use





Productos



Soluciones



Soporte



Socio



Noticia &
Eventos



Quién
somos



Latin America - Español

HDCVI

Recorders

Saber más

© 2010-2024 Dahua Technology Co., Ltd

浙ICP备07004180号-3 浙公网安备 33010802004137号

